

# CoolFlex™ Standard Ventilation Duct



Our **CoolFlex™ Standard Duct** is built with durable PVC laminated fabric, precision-welded to maximize airflow and minimize leakage. Light-weight, rugged and versatile, it performs in the harshest conditions, withstanding temperatures from -20° to 180°F. Each duct is reinforced with heavy-duty spiral wire and delivers dependable toughness while maintaining maximum flexibility.



## Specifications

<b>Fabric Type</b>	Translucent Laminated PVC
<b>Fabric Weight</b>	10 oz. 14 oz. (Upon Request)
<b>Temperature</b>	-20 to 180 F°
<b>Length</b>	25 ft.
<b>Diameter</b>	12 - 24 in.
<b>Pitch</b>	3 - 7 in.
<b>Wire</b>	Steel
<b>Colors</b>	10 oz: White 14 oz: Yellow, Blue
<b>Bond Construction</b>	Welded (Sewn Upon Request)
<b>Custom Finishes</b>	Belt Cuff, Hoop Cuff, Pin-Lock Cuff, and Worm-Gear Cuff
<b>Wear Strip (Optional)</b>	White, Black, Blue, Yellow

*Custom lengths, diameters, and colors available upon request.*

## Features

- Flexible, light-weight, and versatile for a wide range of applications
- Low thermal conductivity with our UV stabilized fabric
- Handles harsh environments with mold and mildew resistant fabric

## Markets & Applications

- Construction and Restoration
- Disaster Relief and Emergency Response
- Rental, Tent, and Structure
- Temporary Heating and Cooling
- Air Conditioning and Spot Cooling
- Ambient Air Distribution
- Dehumidification
- Utility Blowers

