

DynaFlex™

Hi-Temp Ventilation Duct



Our **DynaFlex™ Hi-Temp Duct** is built for extreme air temperatures. Available in silicone-coated fiberglass fabric or polywoven fabric, both duct options deliver exceptional thermal stability with efficient airflow, excellent durability, and resistance to external heat.



Specifications

Fabric Type	Silicone-Coated Fiberglass	Polywoven
Fabric Weight	14 oz.	10 oz.
Temperature	Up to 550 F°	Up to 350°F
Length	25 ft.	25 ft.
Diameter	12 - 24 in.	12 - 24 in.
Pitch	4 - 7 in.	4 - 7 in.
Wire	Steel	Steel
Colors	White, Black	Black
Bond Construction	Sewn	Sewn
Custom Finishes	Belt Cuff, Hoop Cuff, Pin-Lock Cuff, and Worm-Gear Cuff	Belt Cuff, Hoop Cuff, Pin-Lock Cuff, and Worm-Gear Cuff
Wear Strip (Optional)	White, Black, Blue, Yellow	White, Black, Blue, Yellow

Custom lengths, diameters, and wear strip colors available upon request.

Features

- Excellent heat stability and resistance to extreme temperatures
- High strength sewn construction, suitable for many applications
- High durability to abrasion, corrosion, tearing, and mold or mildew resistant
- Flame Resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Specifications

Markets & Applications

- Construction and Restoration
- Disaster Relief and Emergency Response
- Rental, Tent, and Structure
- Temporary Heating and Cooling
- Air Conditioning and Spot Cooling
- Ambient Air Distribution
- Dehumidification
- Utility Blowers